

Horns

L-Series horns increase application flexibility for indoor or outdoor installations. Intended for full building notification as well as on the property ground, they produce a loud sound to notify occupants to evacuate the buildings. Installers can easily adapt devices to suit a wide range of application requirements by using field-selectable sound patterns and volume settings. Compatible with 12- or 24-volt systems. The universal mounting plate's plug-in design simplifies installation, too. L-Series horns are listed to UL 464 for public mode application.



Wall-Mount Horns

Location	Red Model No.	White Model No.	Description
Indoor	HRL	HWL	Horn
Indoor	HGR	HGW	Horn, compact

Horn Strobes

L-Series horn strobes are rich with features guaranteed to cut installation time and maximize profits. Intended for full building notification as well as on the property ground, they produce a loud sound to notify occupants to evacuate the buildings; the strobe is intended to notify those that may have a hearing impairment. Features include a universal mounting plate with a preliminary snap-in feature to hold the product in place for the screw attachment, 7 field-selectable candela settings for wall and ceiling mount devices, and rotary switches to select horn tone and volume settings. Compatible with 12- or 24-volt systems. L-Series horn strobes are listed to UL 1971 and UL 464 for public mode evacuation.



Ceiling-Mount Horn Strobes

Location	Red Model No.	White Model No.	Candela Settings	Marking	Description
Indoor	PC2RL	PC2WL	15, 30, 75, 95, 115, 150, 177	FIRE	2-Wire, Clear Lens
Indoor	PC4RL	PC4WL	15, 30, 75, 95, 115, 150, 177	FIRE	4-Wire, Clear Lens



Wall-Mount Horn Strobes

Location	Red Model No.	White Model No.	Candela Settings	Marking	Description
Indoor	P2RL	P2WL	15, 30, 75, 95, 110, 135, 185	FIRE	2-Wire, Clear Lens
	P2GRL	P2GWL	15, 30, 75, 95, 110, 135, 185	FIRE	2-Wire, Clear Lens, compact
	P2RL-SP	P2WL-SP	15, 30, 75, 95, 110, 135, 185	FUEGO	2-Wire, Clear Lens
Indoor	P4RL	P4WL	15, 30, 75, 95, 115, 150, 185	FIRE	4-Wire, Clear Lens

Note: -SP denotes "FUEGO" printed housing.



Plain Wall-Mount Horn Strobes

Location	Red Model No.	White Model No.	Candela Settings	Marking*	Description
Indoor	P2RL-P	P2WL-P	15, 30, 75, 95, 110, 135, 185	None	2-Wire, Clear Lens

Notes:

- P denotes plain devices with no markings.
- *Compatible with BZR, BZRC, BZSPR, BZSPRC bezels for red devices (white letters) and BZW, BZWC, BZSPW, BZSPWC for white devices (red letters).