

Valves & Fittings

BPV SERIES BULLET® PIERCING VALVES

The ONLY Valve with a Permanent Type, Patented Gasket Application!

- Patented Valve Gasket Application Provides 50 Times More Sealing Area than Competitive "O" Ring Types
- A Sealing Force of Over 180 Inch lbs., Torque Tested with 500 lbs., Pressure Tested at 250°F
- Precision Piercing Needle is Engineered for Concentricity and Hardness to Insure Perfect Seating Every Time
- Nonpositional Mounting - No Adapter Valve Required
- Requires Only a 2" Clearance Area for Installation and Operation
- Hex Key Wrench Included - No Additional Tools Required
- Corrosion Resistant Plated

PART NO.	O.D. TUBING SIZE	PACKAGING
BPV31*	1/4", 5/16", 3/8"	12/Box
BPV31D*	1/4", 5/16", 3/8"	48/Box
BPV21*	1/2", 5/8"	8/Box
BPV36	3/16"	12/Box
BPV56	5/16"	12/Box
BPV38	3/8"	12/Box
BPV12	1/2"	8/Box
BPV58	5/8"	8/Box
BPV34	3/4"	1/Box
BPV78	7/8"	1/Box

*NOTE: BPV31 and BPV21 are furnished with adapter sleeves for indicated multiple use applications.



A1 & A2 ADJUSTABLE LINE TAP VALVES

Signature Series of Clamp-On Line Tap Valves Provide Easy Access to System Refrigerant Without Having to Evacuate System.

- Patent Depressor Valve Action
- Mounts in Any Position
- Retracting Needle for Maximum Flow
- Designed for Permanent Use on System
- Hex Wrench and Adapter Sleeves Included

PART NO.	TUBE SIZE OD (IN.)
A1	1/4, 5/16, 3/8
A2	1/2, 5/8



CA1 ACCESS CONTROL VALVE

Controls the Flow of All 1/4" SAE Male Flare Depressor Type Valves.

- Purging Port for Air Removal and Safety
- Steel Construction
- Use with Standard Charging Hose

