



## MINI-SPLIT CONDENSATE DRAIN HOSE

### Condensate Drain Hose

Non-Insulated

Code	ID	Length	Ctn Qty	Ctn Wt
83001 (DH-14) STANDARD	1/2 in	164 ft	1	6 lbs.
83002 (DH-16) STANDARD	5/8 in	164 ft	1	7 lbs.
83003 (DH-16S) STANDARD	5/8 in	20 ft	5	6 lbs.
83004 (DHQ-16) UV RESISTANT	5/8 in	164 ft	1	6 lbs.
83005 (DSB-16) SMOOTH BORE	5/8 in	65 ft	1	2 lbs.



Non-Insulated

UV Resist

Smooth Bore



**Smooth Bore (DSB-16)**  
Reduces resistance and maximizes condensate flow. Resists clogging.

**UV Resistance (DHQ-16)**  
Resists deterioration from sunlight.

### Condensate Drain Hose

Insulated

Code	ID	Length	Ctn Qty	Ctn Wt
83011 (DSH-14)	1/2 in	65 ft	1	7 lbs.
83012 (DSH-20N)	3/4 in	65 ft	1	10 lbs.
83013 (DSH-25N)	1 in	65 ft	1	13 lbs.



Insulated



**Insulated**  
Protects hose from sweating that can occur from cooler condensate and warmer ambient air.

### Condensate Drain Hose

Insulated Drain-up Hose Kit

Code	Description	Qty.
84306	DSH-UP20E20E-07 Elbow to Elbow 27.5"	10
84307	DSH-UP20E20E-10 Elbow to Elbow 40"	10
84308	DSH-UP20E20S-07 Elbow to Straight Coupler 27.5"	10
84309	DSH-UP20E20S-10 Elbow to Straight Coupler 40"	10

**FEATURES**

- Exclusive hose for drain-up piping
- Easy to adjust position
- Pre-connected hose with fittings

**APPLICATION** • Drain-up hose kit for indoor A/C unit. These insulated drain hoses will greatly reduce install time, since there is no need to cut and cement plastic pipes for the drain assembly.

**RECOMMENDED FOR**

- Exclusive for indoor use
- Commercial HVAC units
- Ceiling cassette
- Ducted concealed

