

All metal gauges with high impact clear view Lexan lens, full size brass movements and recalibrating screw. Available for compound and pressure in assorted sizes and options for use, visibility and refrigerant type. Metric gauges and replacement lenses also available; contact customer service.



PART NO.		SIZE	DESCRIPTION	REFRIGERANTS													
COMPOUND	PRESSURE			R12	R22	R32	R134A	R-290	R404A	R407A	R407C	R410A	R422B	R427A	R502	R507A	R600A
M2-250	M2-500	2-1/2" (63.5mm)	Non-illuminating, Standard	•	•											•	
M2-350	M2-355	2-1/2" (63.5mm)	Non-illuminating, Standard				•										
M2-400	M2-405	4" (102mm)	Illuminating, Class 1, 1%		•		•		•		•						
M2-410	M2-415	2-1/2" (63.5mm)	Non-illuminating, Standard								•						
M2-420	M2-425	2-1/2" (63.5mm)	Non-illuminating, Standard				•		•								•
M2-430	M2-435	2-1/2" (63.5mm)	Non-illuminating, Standard		•		•		•								
M2-460	M2-465	2-1/2" (63.5mm)	Non-illuminating, Standard		•				•		•						
M2-600	M2-605	3-1/8" (80mm)	Illuminating, Class 1, 1%				•		•								•
M2-800	M2-805	3-1/8" (80mm)	Illuminating, Standard	•	•												•
M2-810	M2-815	3-1/8" (80mm)	Non-illuminating, Standard								•						
M2-820	M2-825	3-1/8" (80mm)	Illuminating, Standard		•				•		•						
M2-820L	M2-825L	3-1/8" (80mm)	LED, Standard		•				•		•						
M2-826	M2-827	3-1/8" (80mm)	Illuminating, Standard		•		•				•						
M2-828	M2-829	3-1/8" (80mm)	Illuminating, Standard								•		•	•			
M2-830	M2-831	3-1/8" (80mm)	Illuminating, Standard		•						•	•					
M2-851	M2-856	3-1/8" (80mm)	Illuminating, Standard		•		•		•								
M2-860	M2-865	3-1/8" (80mm)	Liquid Filled, Class 1, 1%		•		•		•		•						
M2-870	M2-875	3-1/8" (80mm)	Liquid Filled, Class 1, 1%	•	•												•
M2-880	M2-885	3-1/8" (80mm)	Liquid Filled, Class 1, 1%		•		•		•								
M2-890	M2-895	3-1/8" (80mm)	Liquid Filled, Class 1, 1%		•				•		•						
M2-924	M2-925	3-1/8" (80mm)	Illuminating, Class 1, 1%		•				•		•						
M2-924CM	M2-925CM	3-1/8" (80mm)	Illuminating, Class 1, 1%, Camo		•				•		•						
M2-951	M2-956	3-1/8" (80mm)	Illuminating, Class 1, 1%		•		•		•								
QC-G430	QC-G434	2-1/2" (63.5mm)	Single Test, Standard		•		•		•								
QC-G460	QC-G465	2-1/2" (63.5mm)	Single Test, Standard		•				•		•						
QC-G820	QC-G825	3-1/8" (80mm)	Single Test, Standard		•				•		•						
QC-G851	QC-G856	3-1/8" (102mm)	Single Test, Standard		•			•	•								

Gauges indicated as Standard are accuracy rated 3-2-3%
 Note: Gauges and hoses not specified for use with R410A can damage product and cause injury.

Gauge Boots and Lenses

Protective gauge boots add increased durability to manifold gauges. Available for 2-1/2" and 3-1/8" gauges.



MR-596

PART NO.	DESCRIPTION
MR-590	2-1/2" Black boot (single)
MR-593	3-1/8" Black boot (single)
MR-594	3-1/8" Red boot for M2-865 liquid filled (single)
MR-595	3-1/8" Blue boot for M2-860 liquid filled (single)
MR-596	Set of two 3-1/8" black boots
MR-598	Set of two black 2-1/2" black boots
MR-517	2-1/2" Screw-on lens fits both plastic and metal gauges
MR-533	3-1/8" Snap-on lens