
## Flaretite®

## 45° Refrigeration & Gas SAE Flare Fitting Seals

Code	Description	Qty.
97210	Combo Kit - 9 seals each of sizes 1/4", 3/8", 1/2", 5/8" (36 seals total)	6 kits/case
97211	Combo Kit - (2) 3/8", (2) 3/4"	10 kits/case
97212	Combo Kit - (2) 3/8", (2) 5/8"	10 kits/case
97213	Combo Kit - (2) 3/8", (2) 1/2"	10 kits/case
97214	Combo Kit - (2) 1/4", (2) 5/8"	10 kits/case
97215	Combo Kit - (2) 1/4", (2) 1/2"	10 kits/case
97216	Combo Kit - (2) 1/4", (2) 3/8"	10 kits/case
97217	(10) 3/4" Seal Kit	10 kits/case
97218	(10) 5/8" Seal Kit	10 kits/case
97219	(10) 1/2" Seal Kit	10 kits/case
97220	(10) 3/8" Seal Kit	10 kits/case
97221	(10) 1/4" Seal Kit	10 kits/case
97222	(200) 5/8" Seal Kit	4 kits/case
97223	(200) 1/2" Seal Kit	4 kits/case
97224	(200) 3/8" Seal Kit	4 kits/case
97225	(200) 1/4" Seal Kit	4 kits/case
97226	(100) 3/4" Seal Kit	4 kits/case
97227	(100) 5/8" Seal Kit	4 kits/case
97228	(100) 1/2" Seal Kit	4 kits/case
97229	(100) 3/8" Seal Kit	4 kits/case
97230	(100) 1/4" Seal Kit	4 kits/case



**APPLICATION** • Used to prevent leaks that are caused by galling, vibration, pulsation & extreme temp changes • A perfect solution for a leak free connection in today's harshest environments • Use with all common refrigeratns

## RECOMMENDED FOR

- Service & repair
- Mini-Split & VRF installations
- Commercial chillers & coolers
- Marine & aviation refrigeration

## FEATURES

- 45° Copper Stamping with Loctite coating
- Locking tabs clip seal securely on fitting
- $\boldsymbol{\cdot}$  Conical rings for multiple points of contact
- Made for all common 45° fittings
- Rated for -40°F to 300°F
- Pressure rated up to 10,000 psi

