

Industrial / Commercial Products

100% SILICONE SEALANT INDUSTRIAL GRADE RTV

High performance sealing and glazing compound that is ideal for use in most OEM and maintenance applications. Forms a strong, durable and weather-resistant seal and provides excellent adhesion to most non-porous surfaces. 50 year warranty. Solvent clean up. NSF listed.

08160I - 10.1 Fl. Oz. (300 mL) - White

08162I - 10.1 Fl. Oz. (300 mL) - Almond

08164I - 10.1 Fl. Oz. (300 mL) - Bronze

08165I - 10.1 Fl. Oz. (300 mL) - Gray

08166I - 10.1 Fl. Oz. (300 mL) - Black

08260I - 10.1 Fl. Oz. (300 mL) - Clear

Meets or exceeds the requirements of TT-S-00230C, TT-S-001543A, C.G.S.B. 19C9-9, Din 18540 Part 2, Mil. Spec 46106A, CEBTP 432.65 140-2, ASTM C920. USDA authorized for use in federally inspected meat and poultry plants.



EXTREME TEMPERATURE HVAC/R SILICONE SEALANT

Made especially for HVAC/R applications, this premium sealant provides a long-lasting, weather-resistant seal and offers excellent adhesion, flexibility and durability. Use on air conditioners, ducts, furnaces, water heaters, refrigerators, vents and more. Adheres well to metal and most other building materials and remains flexible from -60°F to 400°F.

0896 - 280 mL - White

089650 - 280 mL - Aluminum

0897 - 280 mL - Clear

Meets or exceeds Federal Specifications TT-S-00230C, Class A, TT-S-001543A Class A, ASTM C920.



100% SILICONE SEALANT HEAT RESISTANT RTV

Formulated with iron oxide to resist extreme heat exposure. Withstands temperatures up to 600°F and can be used on industrial ovens, heating elements, boilers, and more. 50 year warranty. Solvent clean up.

08090I - 10.1 Fl. Oz. (300 mL) - Red

08290I - 2.8 Fl. Oz. (83 mL) - Red

Meets or exceeds the requirements of TT-S-00230C, TT-S-001543A, C.G.S.B. 19C9-9, Din 18540 Part 2, Mil. Spec 46106A, CEBTP 432.65 140-2, ASTM C920. USDA authorized for use in federally inspected meat and poultry plants.



SILICONIZED ACRYLIC CAULK CONSTRUCTION GRADE - 35 YEAR

Superior sealant fortified with silicone for increased flexibility and extended life. It provides excellent adhesion to most interior and exterior surfaces. Mildew resistant, low-odor and low-VOC. 35 year warranty. Water clean up.

08460I - 10.1 Fl. Oz. (300 mL) - White

08462I - 10.1 Fl. Oz. (300 mL) - Almond

08464I - 10.1 Fl. Oz. (300 mL) - Brown

08465I - 10.1 Fl. Oz. (300 mL) - Gray

08466I - 10.1 Fl. Oz. (300 mL) - Black

08760I - 10.1 Fl. Oz. (300 mL) - Clear

Meets or exceeds the requirements of ASTM C834.



BUTYL RUBBER SEALANT ARCHITECTURAL GRADE

A high-performance, pliable sealant that is ideal for tough outdoor jobs and below-grade applications. Use indoors or outdoors, wherever a durable, flexible and water-tight seal is required. Butyl rubber sealant adheres to most building surfaces and remains rubbery and flexible. Paintable. 10 year warranty.

06970I - 10.1 Fl. Oz. (300 mL) - White

0697GI - 10.1 Fl. Oz. (300 mL) - Gray

Meets or exceeds the requirements of Federal Specifications TT-S-001657, TT-C-00598C, TT-C-1796A.



FIRESTOP LC150RD SEALANT

Intumescent, high-solids firestop compound that effectively seals penetration openings against the spread of fire, smoke, toxic gases and water when applied properly. Endothermic fillers absorb heat and release water and the high solids formula means no shrinkage. Withstands temperatures up to 1000°F and is up to 2 hour fire rated. Sandable and paintable. Water clean up.

LC150RD - 9.0 Fl. Oz. (266 mL) - Red

Meets Fed. Specs. ASTM E-814 (UL 1479) and ASTM E-84 (UL 723) and many UL classifications.

