AG-4200E

Electronic condensate management sensor system

Code	Description	Qty.
96143	Primary Pan Sensor	1



25XE UL 508

FEATURES

- Switch can be normally open or normally closed
- 5 amp, 24 volts AC solid state sensor with water detection LED light
- · Adjustable height mount
- · 6 feet of control wire
- UL 508

US Patent 8,317,16970

APPLICATION • Multipurpose Condensate Overflow Sensor that combines the proven water sensing technology of the AG-1250E with our industry leading Goliath and Titan drain pan line to deliver the ultimate condensate management system. The AG-4200E is the complete condensate management system for Goliath, Goliath Furnace, Goliath Value Series and Titan Drain Pans • 24 VAC, 5 Amp • Controls Normally Open or Normally Closed • 6' of Standard Control Wire • Compact Waterproof Design • Includes **Vibration Isolators**



AG-4200M

Magnetic condensate management system

Code	Description	Qty
96142	Primary Pan Sensor	1



FEATURES

- · Easy, Drill-Free Installation
- Pull Up Test Knob
- Water detection LED light
- · Protective Cover
- UL 508

US Patent 8,578,770; 8,317,1690

APPLICATION • Multipurpose condensate overflow sensor that combines the incredibily easy to install AG-1100+ with our industry leading Goliath and Titan drain pan line to deliver the ultimate condensate management system. It can be mounted to the drain pan in 10 seconds or less. Installation does not require any pre-drilling for screws. The AG-1100+ incorporates a protective cover to keep out insulation and debris that could prevent the float from rising. The AG-4200M is the complete condensate management system for Goliath, Goliath Furnace, Goliath Value series and Titan Drain pans.

• 3/4" PVC threaded male pipe adapter • Normally Open 3rd Wire for Optional External Alarm, Digital Controller, or Energy Management System • Residential and Commercial • High Capacity 5 Amp, 24 Volt AC Magnetic Float Switch

Includes Vibration Isolators

