



60T ELECTRICAL RATING:
TYPICAL ELECTRICAL RATINGS TEMP RANGE: -40°F TO 350°F

GENERAL PURPOSE LIMITS L & LD SERIES

- Open on Rise
- Close when Temperature Differential is Reached
- 1/4" Quick Disconnect Terminals
- Use 60T Electrical Ratings

Volts (VAC)	Resistive (Non-Inductive)	Motor Rating (Inductive)		
		Full Load	Locked Rotor	Pilot Duty
120	25A	14A	72A	125VA
240	25A	10A	60A	125VA

350°F Max Ambient Temperature


"L" SERIES, SINGLE POLE- SINGLE THROW STYLE 60T11



Part No.	°Diff.	Open (°F)	Close (°F)
L120	10	120	110
L125	10	125	115
L130	15	130	115
L135	15	135	120
L140	20	140	120
L145	20	145	125
L150	20	150	130
L155	20	155	135
L160	20	160	140
L165	20	165	145
L170	20	170	150
L175	20	175	155
L180-20	20	180	160
L180-40	40	180	140

Part No.	°Diff.	Open (°F)	Close (°F)
L190	40	190	150
L200	40	200	160
L205	40	205	165
L225	40	225	185
L240	40	240	200
L250	40	250	210
L260	40	260	220
L270	40	270	230
L290	40	290	250
L300	40	300	260
L320	40	320	280
L340	40	340	300

"LD" SERIES SINGLE POLE-DOUBLE THROW STYLE 60T13



Part No.	Description	Open (°F)	Close (°F)	Diff.
LD120	SPDT Thermostats	120	105	15
LD135	SPDT Thermostats	135	120	15
LD140	SPDT Thermostats	140	120	20
LD145	SPDT Thermostats	145	125	20
LD155	SPDT Thermostats	155	135	20
LD170	SPDT Thermostats	170	150	20
LD200	SPDT Thermostats	200	160	40
LD225	SPDT Thermostats	225	185	40
LD270	SPDT Thermostats	270	230	40

ADJUSTABLE AT SERIES



- Series Covers Almost 95% of Heater and Dryer Applications
- Dial Knob
- 40° Adjustable Range
- 1/4" Quick Connect Terminals
- Use 60T Electrical Ratings

OPEN ON TEMPERATURE ADJUSTABLE THERMOSTATS STYLE 74T11

Part No.	Adjustable Range (°F)	Adjustable Range (°F)	Diff.
AT012	135	175	20
AT013	175	215	40
AT014	210	250	40
AT015	250	290	40

CLOSE ON TEMPERATURE ADJUSTABLE AIRFLOW THERMOSTATS STYLE 74T11

Part No.	Adjustable Range (°F)	Adjustable Range (°F)	Diff.
AT021	90	130	20
AT022	140	180	20